## 2022



## **HIGHLIGHTS**

- Rotax® V-Twin engine options
- Front and rear FOX 1.5 PODIUM QS3 shocks
- Visco-4Lok† front differential
- Intelligent Throttle Control (iTC™) with riding modes
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
- 3,500 lb (1,588 kg) winch
- 14 in. cast-aluminum beadlock wheels
- 26 in. ITP Terracross radial tires
- · Painted plastics for premium look
- · Heavy-duty front and rear bumpers
- · Aluminum taper-profile handlebar with full-wrap handguards
- · Multifunction digital gauge
- Convertible Rack System (CRS) with LinQ<sup>™</sup> system
- · Dynamic passenger comfort ergonomics
- Multiposition passenger hand grips
- · Raised floorboards



Iron Gray, Black & Neo Yellow / 850 / 1000R

ENGINES	850	1000R
Туре	78 hp, Rotax 854 cc V-twin, liquid-cooled	91 hp, Rotax 976 cc V-twin, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	
Transmission	CVT, P/R/N/H/L, standard engine braking	
Drive Train	Selectable 2WD/4WD/Lock 4WD with Visco-4Lok front differential	
Power Steering	Tri-Mode Dynamic Power Steering (DPS)	
SUSPENSIONS		
Front Suspension	Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel	
Front Shocks	FOX 1.5 PODIUM QS3	
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.9 in. (25.1 cm) travel	
Rear Shocks	FOX 1.5 PODIUM QS3	
TIRES & WHEELS		
Front Tires	ITP Terracross 26 x 8 x 14 in.	
Rear Tires	ITP Terracross 26 x 10 x 14 in.	
Wheels	14 in. cast-aluminum beadlock	
BRAKES		
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers	
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper	

DIMENSIONS & CAPACITIES	850	1000R
Estimated Dry Weight*	874 lb (396 kg)	900 lb (408 kg)
LxWxH	94 x 48 x 53 in. (238.8 x 121.9 x 135 cm)	
Wheelbase	59 in. (149.9 cm)	
Ground Clearance	11 in. (27.9 cm)	
Seat Height	34.5 in. (87.7 cm)	
Rack Capacity	Front: 100 lb (45 kg)/Rear: 200 lb (90 kg)	
Storage Capacity	Rear: 5.7 gal (21.4 L)	
Towing Capacity	1,650 lb (750 kg)	
Fuel Capacity	5.4 gal (20.5 L)	
FEATURES		
Gauge	7.6 in. wide digital display: speedometer, tachometer, odometer, trips and hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge and clock	
Instrumentation	Lighter-type DC outlet in console, standard connector in the back (15 A)	
Anti-Theft System	RF Digitally Encoded Security System (D.E.S.S.™)	
Lighting	230 W from twin 60 W projectors and dual 55 W reflectors with tail light/brake light	

## Protection Heavy-duty front and rear bumpers Aluminum taper-profile handlebar with full-wrap handguards Mudguards **WARRANTY & EXTENDED SERVICE** 6-month BRP limited warranty **Factory Warranty** B.E.S.T. term available up to 36 months

3,500 lb (1,588 kg) winch Convertible Rack System (CRS)



Winch

**Extended Service Terms** 

Seat