

## can-am. **OUTLANDER 6X6 XU+ 450 T**

## **HIGHLIGHTS**

- Rotax® single cylinder engine
- Continuously Variable Transmission (CVT) with extra low L-gear
- 3,500-lb (1,588 kg) winch
- · Speed limiter
- Heavy-Duty front bumper
- 26-in. (66 cm) Carlisle ACT HD 6-ply tires
- 12-in. (30.5 cm) cast-aluminum wheels Tri-Mode Dynamic Power Steering (DPS™)
- Heated grips & throttle
- Double Torsional Trailing arm Independent (TTI2) rear suspension
- Quick release sway bar
- Double A-arm front suspension
- · Relocated air intakes
- RF Digitally Encoded Security System (D.E.S.S.™)
- 2.9-gal (10.9 L) water-resistant rear compartment
- Cargo extenders
- 159 kg capacity rear bed with cargo extenders



ENGINE	
Туре	28 kW (38 hp), Rotax® 427 cc single cylinder,
	liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 4WD / 6WD with Visco-Lok† QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed Category	Up to 60 km/h
SUSPENSIONS	
Front Suspension	Double A-arm 9 in. (22.9 cm) travel
Front Shocks	Oil
Rear Suspension	Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 8.8 in. (22 cm) travel
Rear Shocks	Oil
TIRES / WHEELS	
Front Tires	Carlisle† ACT HD 26 x 8 x 12 in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle† ACT HD 26 x 10 x 12 in. (66 x 25.4 x 30.5 cm)
Wheels	12-in. (30.5 cm) cast-aluminum
BRAKES	
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper

DIMENSIONS / CAPACITIES	
Estimated Dry Weight *	443 kg
LxWxH	279 x 118.8 x 124 cm
Wheelbase	208 cm
Ground Clearance	26.7 cm
Seat Height	85.8 cm
Rack Capacity	Front: 54 kg /
	Rear: 159 kg
Storage Capacity	Rear: 2.9 gal (10.9 L)
Towing Capacity	907 kg trailer with brakes
	465 kg trailer without brakes
Fuel Capacity	20.5 L
FEATURES	

Gauge	4.5 in. digital display:
	Speedometer, tachometer, odometer, trip & hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge & clock
Instrumentation	Lighter type DC Outlet in console, standard connector in the back (15-A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Lighting	70 W from dual 35-W front light and dual 55-W reflectors with tail light / brake light
Winch	3,500-lb (1,588 kg) winch
T-Category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn
Seat	Reinforced seat skin
Protection	Heavy-Duty front bumper, Central skid plate, heated grips
WARRANTY	
Factory warranty	2-year BRP limited warranty

