

MY24 OUTLANDER 6X6 XU+ 1000 T



 Boreal Green

HIGHLIGHTS

- Selectable 4WD / 6WD with Visco-4Lok† auto-locking front differential
- Tri-Mode Dynamic Power Steering (DPS)
- Continuously Variable Transmission (CVT) with extra low L-gear
- 14 in. (35.6 cm) aluminum wheels
- 26 in. (66 cm) ITP Terracross tires
- 3,500-lb (1,588 kg) winch
- Dump dual-level cargo box with modular accessories
- Heated grips and throttle
- Speed limiter
- RF Digitally Encoded Security System (D.E.S.S.™)
- Painted plastics for premium look

| ENGINE | 1000 |
|----------------------|---|
| Type | 60 kW (80 hp), Rotax® 976 cc V-twin, liquid cooled |
| Fuel Delivery System | Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI) |
| Transmission | CVT Extra low L / H / N / R / P |
| Drive Train | Selectable 4WD / 6WD / Lock 4WD with Visco-4Lok front differential |
| Driving Assistance | Work / Standard / Sport modes Intelligent Engine Braking (iEB™) Speed limiter |
| Power Steering | Tri-Mode Dynamic Power Steering (DPS) |
| Speed Category | Up to 60 km/h |

| SUSPENSIONS | |
|------------------|--|
| Front Suspension | Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel |
| Front Shocks | Twin tube |
| Rear Suspension | Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 9.9 in. (25.1 cm) travel |
| Rear Shocks | Twin tube |

| TIRES / WHEELS | |
|--------------------|--|
| Front & Rear Tires | ITP† Terracross 26 x 8/10 x 14 in. (66 x 20.3 / 25.4 x 35.6 cm) |
| Wheels | 14 in. (35.6 cm) cast-aluminum |

| BRAKES | |
|--------|---|
| Front | Dual 214 mm disc brakes with hydraulic twin-piston calipers |
| Rear | Dual 214 mm disc brakes with hydraulic twin-piston calipers |

| DIMENSIONS / CAPACITIES | |
|-------------------------|---|
| Estimated Dry Weight * | 576 kg |
| L x W x H | 297 x 122 x 149.4 cm |
| Wheelbase | 208 cm |
| Ground Clearance | 27.9 cm |
| Seat Height | 87.7 cm |
| Rack Capacity | Front: 45 kg / Rear: 318 kg |
| Storage Capacity | Dual-level cargo box with sidewalls and tailgate Rear: 18.5 gal (70 L) |
| Towing Capacity | 2,000 lb (907 kg) trailer with brakes and 1,486 lb (674 kg) trailer without brakes |
| Fuel Capacity | 5.4 gal (20.5 L) |

| FEATURES | |
|---------------------|---|
| Gauge | 4.5 in. digital display |
| Instrumentation | DC Outlet, 15-A connector |
| Ignition | RF Digitally Encoded Security System (D.E.S.S.™) |
| Lighting | LED headlights |
| Winch | 3,500-lb (1,588 kg) winch |
| T-Category features | Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn |
| Seat | Reinforced seat skin |
| Handlebar | Standard with heated grips & throttle |
| Protection | Heavy-duty front bumper |

| WARRANTY | |
|------------------|-----------------------------|
| Factory warranty | 2-year BRP limited warranty |



©2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †All trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by the age of 16 and older. Never carry passengers on any ATV not specifically designated for such use. Some models depicted may include optional equipment.



REQUEST A QUOTE

