

MY24 TRAXTER DPS HD9



 Tundra Green

ENGINE

Type	48 kW (65 hp) / 59 lb-ft, Rotax® 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PRO-TORQ CVT Transmission with Quick Response System (QRS), high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P
Drive Train	Selectable Turf Mode / 2WD / 4WD with Visco-Lok† auto-locking front differential
Driving Assistance	Electronic Hill Descent Control ECO™ / ECO™ Off / Work modes
Power Steering	Dynamic Power Steering (DPS™)

SUSPENSIONS

Front Suspension	Double A-arm / 10 in. (25.4 cm) travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	TTA with external sway bar / 10 in. (25.4 cm) travel
Rear Shocks	Twin tube gas charged shocks

TIRES / WHEELS

Front & Rear Tires	XPS Trail Force 27 x 9 / 11 x 14 in. (68.6 x 22.9 / 27.9 x 35.6 cm)
Wheels	14 in. (35.6 cm) cast-aluminum

BRAKES

Front	Dual 220 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm disc brakes with hydraulic single-piston calipers

HIGHLIGHTS

- Dynamic Power Steering (DPS)
- 14 in. (35.6 cm) cast-aluminum wheels
- 27 in. (68.6 cm) XPS Trail Force tires
- Horn & side mirrors

DIMENSIONS / CAPACITIES

Cage	Profiled cage. ROPS approved
Estimated Dry Weight *	1,541 lb (699 kg)
L x W x H	121 x 62 x 76 in. (307.1 x 157.5 x 193 cm)
Wheelbase	83 in. (211.5 cm)
Ground Clearance	11 in. (28 cm)
Cargo Box Dimensions	38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm)
Cargo Box Capacity	1,000 lb (454 kg)
Power tilt bed	N/A
Tailgate Load Capacity	250 lb (113.4 kg)
Storage Capacity	Total: 10.4 gal (39.5 L)
Towing Capacity	2,500 lb (1,136 kg)
Payload Capacity	1,500 lb (680 kg)
Fuel Capacity	10.6 gal (40 L)
Person Capacity	3

FEATURES

Gauge	4.5 in. (11.4 cm) wide digital display
Battery	12-V (18 amp/h)
Magneto	650-W
Instrumentation	DC outlet (10-A)
Lighting	Front lighting output 140 W LED tail lights
Winch	N/A
Seat	VERSA-PRO bench seat with passenger seats flipping up, underside hooks
Steering Wheel	Adjustable tilt steering
Protection	Integrated front steel bumper HMWPE central skid plate
Hitch Type	2-in hitch receiver

WARRANTY

Factory warranty	2-year BRP limited warranty
------------------	-----------------------------



REQUEST A QUOTE



©2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.